



## Porty L 1200

Article Number: 4962

- Definitely faster, smaller, lighter, but with stronger output performance than units with lead-gel cell battery
- Only 5,9 kg total weight but 1200 Ws output
- Extremely fast flash recycle times from 0,2 s (L 600)
- Extremely short flash duration up to 1/8100 s (L 600 with Speed Head)
- Choice of symmetric or asymmetric power distribution via the „A“ or „B“ socket  
Individual settings in 1/10 f-stop increments
- Integrated Profoto Air radio, Hensel Strobe Wizard Plus and FREEMASK-receiver, switchable  
Radio remote functions: output adjustment, triggering, modelling light, standby. Full remote control with both systems, manufacturer compatible. Currently included in our Profoto and Phase One offer
- Integrated radio antenna for optimum protection
- Metal housing with sturdy, protective rubber profile
- Special ergonomical handle bar for carrying, with integrated spare fuses
- Optional use of AC mains switch drawer instead of power pack
- Output adjustment in 1/10 f-stop increments
- Output range of 7 f-stops
- Large 7-segment performance indicator
- Connector socket for round plugs / Hensel Porty connector and Pro Mini / 20-pol. long plug via adapter
- USB port for software updates
- Durable foil surface with ‚real‘ push-buttons for ‚feel good‘ use
- New foil surface with clearly detectable imprint around the push-buttons. Optimal for your sense of touch

- Hensel usage concept – name and position of switches and control units are generally the same. Working without rethinking!
- APD, internal power reduction when reducing power output
- Built-in photocell , seperately switchable
- Synchronous socket for standard cord 6,3 mm
- Test button for manual test firing
- Very low synchronous voltage protects digital cameras
- Thermal monitoring of performance electronics
- L x W x H: 19,8 x 22,5 x 21,5 cm Weight: 5,9 kg
- Delivery time: none