



MONO MAX 750

Article Number: 3075

The power pack in the heavyweight class presents itself in absolute top form. Fit and powerful: up to 3 flashes per second at minimum output. Topnotch technology makes handling fast and easy and the practical remote control eliminates excess leg work in the studio. MONO MAX, the champ with top professional features.

- >Digital adjustment precision, up to 1/10 f-stops accuracy for exact repetition
- >Flash output and modeling lamp - proportional or independent adjustment, stepless from 1/32 to 1/1 (6f)
- >Proportional adjustment of modeling lamp in 2 f-stops from MONO MAX 750, MONO MAX 1500 and MONO MAX 3000 - making adaption to different flash units easy
- >Slow recycling for operation on weak mains sources, switchable
- >Additional sync socket included
- >Newly developed handle with integrated spare fuses
- >Bracket with integrated tilting head for smooth panning
- >Optional protective colour-correcting glass Remote Control
- >Output adjustment in 2/10 f-stops (modeling light proportional to flash output)
- >Stand-by function
- >Modeling light ON/OFF
- >Test trigger
- >Additional sync socket
- >Ready indicator
- >5 m cord (possible extension up to 20 m)

Data sheet

Stored energy:	750 J
Recharging up to 1/1:	0,8 s
Recharging up to 1/16:	0,34 s
Flash Duration t 0,5 (1/1 Energy):	1/1000 s
Flash Duration t 0,1 (1/1 Energy):	1/350 s
Power control flash:	in 1/10 f: 6f
Output adjustment modeling light:	off/ full/ prop (1/10)
Remote control:	Cord 5 m, output adj. in f 2/10 , standby, test, mod, lamp, syn.
Weight:	4,3 kg

Measurements, L x W x H: 47,5 x 21x 19,6 cm
Aperture at 1m (2m), 100 f 90,7 (f45,7)
ASA, t 1/60:
Modeling Lamp: 650 W/G 6,35
Plug-in Flash Tube: